COMPARATIVE TABLE OF THE 3 AUTOMATIC POLISHING MODELS





SAFA



MINISAFA



MICROSAFA


FLOW RATE	2,000l/h
FILTRATION	1 particle filter 50µm 1 particle and water absorbent filter 15µm, type FG–300 aluminium
Nr. TANKS	Multiple tanks
RECOMMENDED FOR TANKS	More than 50,000 Lts
PUMP TYPE	Gear pump
NO FLOW ALARM	Yes
WATER ALARM	Yes
HIGH PRESSURE ALARM	Yes
INCLUDES LEAK DETECTOR	Yes
INGRESS PROTECTION RATING - IP	55
SUCTION-PRESSURE CONNECTION	1,5" to 2"
DIGITAL PRESSURE SWITCH	No
FLOW SWITCH	No
ANALOG PRESSURE SWITCH 0-10bar	Yes
COUNTER	Yes - MGI 110
WATER VIEWER	Yes
ACHIQUE PUMP	Yes
MONITORING AND CONTROL BOX TO VALVES	Yes
PORTABLE VERSION AVAILABLE	Yes
DIMENSIONS	1300x1100x560

3,000	0I/h
Particle filter 50µm (strainer)	
FG-:	
1 storage tank	
Up to 50,000 Lts	
Blades pump	
Ye	es .
Ye	es
Ne	0
Ne	0
55	5
1'	п
Ne	0
Ye	es .
Ne	0
Ne	0
Ye	es .
Ne	0
Ne	0
Ye	es .
500x50	0x650

20 l/h
Particle filter $100\mu m$ Water decanting
1 day tank
Up to 1,000 Lts
Solenoid piston pump
Yes
Yes
No
No
66
1/4"
Yes
No
No
No
Yes
No
No
No
400x300x150









STANDARD FEATURES
Control panel / Alarm digital contacts
Time switch/ NFC Relay setting
50 / 5 micron 2 stage filtration
Filtration to 1 tank
Pump flow rate 3000 I/h





With IP65 enclosure / Weatherpoof



Infrarred Leak Sensor and oil tray
PAMAS Particle Counter
Inprocloud Remote Monitoring
Modbus connectivity for alarms









