

Anglo Nordic Bumer Products Limited
12/14 Island Farm Avenue
West Molesey
Surrey
KT8 2UZ - UK

Tel: +44 (0) 20 8979 0988
Fax: +44 (0) 20 8979 6961
email: sales@anglo-nordic.com
www.anglo-nordic.com

Approved Ball Valves Type GB/BVL & GB/BVT

A range of ball valves designed to meet the requirements of both:

- EN 331:2015 Manually operated ball valves and closed bottom taper plug valves for gas installations in buildings
- United Kingdom Water Supply (Water Fittings) Regulations 1999, The Water Byelaws 2014 Scotland and The Water Supply (Water Fittings) Regulations (Northern Ireland) 2009

The valves have been tested by BSI to EN 331:1198/A1:2010 and have been awarded Certificate of Constancy of Performance no 0086-CPR-599951 in compliance with the Construction Products Regulations.

The valves have been certified by the Water Regulations Advisory Scheme (WRAS®), certificate no. 1611070. This applies only to the valves with red and blue handles.

Working condition parameters

	Maximum working pressure	Temperature range
Gas (1 st , 2 nd and 3 rd Gas Families)	5 bar	-5°C to 60°C
Water/Oil	20 bar	-5°C to 150°C

End fittings

The valves are either supplied with internal threads at both ends made to EN 10226 (BSP Parallel) designed to assemble to taper external threads, or else compression end fittings made to EN 1254-2.

Valve Range – Lever handles

Part code			Connection	EN 331 Approved?	WRAS Approved?
Yellow lever	Blue lever	Red lever			
GB/BVL14	GB/BVL14B	GB/BVL14R	EN 10226 Rp1/4	✓	✓
GB/BVL38	GB/BVL38B	GB/BVL38R	EN 10226 Rp3/8	✓	✓
GB/BVL12	GB/BVL12B	GB/BVL12R	EN 10226 Rp1/2	✓	✓
GB/BVL34	GB/BVL34B	GB/BVL34R	EN 10226 Rp3/4	✓	✓
GB/BVL1	GB/BVL1B	GB/BVL1R	EN 10226 Rp1	✓	✓
GB/BVL114	GB/BVL114B	GB/BVL114R	EN 10226 Rp1 1/4	✓	✓
GB/BVL112	GB/BVL112B	GB/BVL112R	EN 10226 Rp1 1/2	✓	✓
GB/BVL2	GB/BVL2B	GB/BVL2R	EN 10226 Rp2	✓	✓
GB/BVL3	GB/BVL3B	GB/BVL3R	EN 10226 Rp3		
GB/BVL15	GB/BVL15B	GB/BVL15R	15mm Compression	✓	✓
GB/BVL22	GB/BVL22B	GB/BVL22R	22mm Compression	✓	✓
GB/BVL28	GB/BVL28B	GB/BVL28R	28mm Compression	✓	✓
GB/BVL35	GB/BVL35B	GB/BVL35R	35mm Compression	✓	✓
GB/BVL42	GB/BVL42B	GB/BVL42R	42mm Compression	✓	✓
GB/BVL54	GB/BVL54B	GB/BVL54R	54mm Compression	✓	✓

n.b. WRAS approval only applies to valves with blue and red levers

Valve Range – T handles

Part code			Connection	EN 331 Approved?	WRAS Approved?
Yellow handle	Blue handle	Red handle			
GB/BVT14	GB/BVT14B	GB/BVT14R	EN 10226 Rp1/4	✓	✓
GB/BVT38	GB/BVT38B	GB/BVT38R	EN 10226 Rp3/8	✓	✓
GB/BVT12	GB/BVT12B	GB/BVT12R	EN 10226 Rp1/2	✓	✓
GB/BVT34	GB/BVT34B	GB/BVT34R	EN 10226 Rp3/4	✓	✓
GB/BVT1	GB/BVT1B	GB/BVT1R	EN 10226 Rp1	✓	✓
GB/BVT15	GB/BVT15B	GB/BVT15R	15mm Compression	✓	✓
GB/BVT22	GB/BVT22B	GB/BVT22R	22mm Compression	✓	✓
GB/BVT28	GB/BVT28B	GB/BVT28R	28mm Compression	✓	✓

n.b. WRAS approval only applies to valves with blue and red handles