GAS VALVES

DUNGS - SUNTEC

	DUNGS	SUNTEC	REMARKS
With pressure regulator	**Fast opening**		
	MB-D 405 B01 S22	M2C52F07	
	MB-D 405 B01 S52	M2C55F07	
	MB-D 407 B01 S22	M2C52F07 - M3C42F07	M3 : max. inlet pressure 160 mbar and class B+B. Depends on the conditions of operation (see operating curve in the product data sheets).
	MB-D 407 B01 S52	M2C55F07 - M3C45F07	
	Slow opening		
	MB-DLE 405 B01 S22	M2C52S07	
	MB-DLE 405 B01 S52	M2C55S07	
	MB-DLE 407 B01 S22	M2C52S07 - M3C42S07	M3 : max. inlet pressure 160 mbar and class B+B. Depends on the conditions of operation (see operating curve in the product data sheets).
	MB-DLE 407 B01 S52	M2C55S07 - M3C45S07	
Without pressure regulator	**Fast opening**		
	DMV-D 503/11	M2N50F07	Different body lengths between SUNTEC (110mm) and DUNGS (77mm), requires adaptation of the piping length.
	DMV-D 507/11	M3N40F07	M3 : max. inlet pressure 160 mbar and class B+B. Different body lengths between SUNTEC (110mm) and DUNGS (93mm), requires adaptation of the piping length.
	Slow opening		
	DMV-DLE 503/11	M2N50S07	Different body lengths between SUNTEC (110mm) and DUNGS (77mm), requires adaptation of the piping length.
	DMV-DLE 507/11	M3N40S07	M3 : max. inlet pressure 160 mbar and class B+B. Different body lengths between SUNTEC (110mm) and DUNGS (93mm), requires adaptation of the piping length.

INTERCHANGEABILITY LIST

HONEYWELL - SUNTEC

	HONEYWELL	SUNTEC	REMARKS
With pressure regulator	**Fast opening**		
	VR415AA	M2C55F07	Different body lengths between SUNTEC (110mm) and HONEYWELL (134mm), requires adaptation of the piping length.
	VR420AA	M3C45F07	M3 : max. inlet pressure 160 mbar and class B+B. Different body lengths between SUNTEC (110mm) and HONEYWELL (134mm), requires adaptation of the piping length.
	Slow opening		
	VR415AB	M2C55S07	Different body lengths between SUNTEC (110mm) and HONEYWELL (134mm), requires adaptation of the piping length.
	VR420AB	M3C45S07	M3 : max. inlet pressure 160 mbar and class B+B. Different body lengths between SUNTEC (110mm) and HONEYWELL (134mm), requires adaptation of the piping length.

KROMSCHRÖDER - SUNTEC

	KROMSCHRÖDER	SUNTEC	REMARKS
With pressure regulator	**Fast opening**		
	CG 1 15 R01DT2	M2C55F07	Different body lengths between SUNTEC (110mm) and KROMSCHRODER (150mm), requires adaptation of the piping length.
	CG 1 20 R01DT2	M3C45F07	M3 : max. inlet pressure 160 mbar and class B+B. Different body lengths between SUNTEC (110mm) and KROMSCHRODER (156mm), requires adaptation of the piping length.